

N 30, integrated cooker hood, 60 cm, silver  
D64MAC1X0B



COOKING PASSION SINCE 1877



B

The Integrated Cooker Hood with a fold out unit is discreetly hidden within the upper cabinets.

✓ LED Lighting – Clear illumination while you cook.

#### Features

##### Technical Data

Typology : Built-in/Built-under  
Approval certificates : CE  
Length electrical supply cord : 150 cm  
Minimum distance above an electric hob : 500 mm  
Minimum distance above a gas hob : 650 mm  
Net weight : 11.9 kg  
Type of control : mechanical  
Number of speed settings : 3  
Maximum output air extraction : 625 m<sup>3</sup>/h  
Maximum output recirculating air : 416 m<sup>3</sup>/h  
Number of lights : 2  
Noise level : 70 dB(A) re 1 pW  
Diameter of air outlet : 150 / 120 mm  
Grease filter material : Washable aluminium  
EAN code : 4242004223375  
Connection Rating : 256 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 50; 60 Hz  
Plug type : GB plug  
Installation typology : Wall-mounted

#### Optional accessories

Z511MA0X0 Standard odor filter (replacement)



4 242004 223375

N 30, integrated cooker hood, 60 cm, silver  
D64MAC1X0B



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m<sup>3</sup>/h
- Noise max. Normal Level: 70 dB\*

### Features

- Push button control operation
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 metal grease filter cassettes

### Design

- Integrated hood
- For installation between cupboards
- Hinged door
- Mechanical controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 68.4 kWh/year\*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

### Optional accessories

- Recirculating kit Z51IMA0X0

\* In accordance with the EU-Regulation No 65/2014

N 30, integrated cooker hood, 60 cm, silver  
D64MAC1X0B

## Dimensioned drawings

