

product information sheet

Trade Mark	Electrolux
Model	EFF80680BX 942492599
Annual Energy Consumption (kWh/year)	51.7
Energy Efficiency class	A
Fluid Dynamic Efficiency	32
Fluid Dynamic Efficiency class	A
Lighting Efficiency (lux/W)	15
Lighting Efficiency class	D
Grease Filtering Efficiency	60
Grease Filtering Efficiency class	E
Air flow at minimum and maximum speed in normal use (m ³ /h)	200/650
Air flow at intensive or boost setting (m ³ /h)	820
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	42/67
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	74
Power consumption in off mode (W)	-
Power consumption in standby (W)	0.49

Attribute Name	Symbol	Value	Unit
Model Denomination		EFF80680BX 942492599	
Annual Energy Consumption	AEC _{hood}	51.7	kwh/a
Time increase factor	f	0.8	
Fluid Dynamic Efficiency	FDE _{hood}	32,0	
Energy Efficiency Index	EEL _{hood}	48.7	
Measured air flow rate at best efficiency point	QBEP	374,0	m ³ /h
Measured air pressure at best efficiency point	PBEP	484	Pa
Maximum air flow	Q _{max}	860,0	m ³ /h
Measured electric power input at best efficiency point	WBEP	157,0	W
Nominal power of the lighting system	WL	8,0	W
Average illumination of the lighting system on the cooking surface	E _{middle}	117	lux
Measured power consumption in standby mode	P _s	-	W
Measured power consumption off mode	P _o	0.49	W
Sound power level	LWA	67	dB

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

- Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished.
- Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
- Replace the charcoal filter(s) when necessary to maintain a good odour reduction efficiency.
- Clean the grease filter(s) when necessary to maintain a good grease filter efficiency.
- Use the maximum diameter of the ducting system indicated in this manual to optimize efficiency and minimize noise.